




L-Bracket



Edge Mount



Yoke Mount



Dimensions

APPLICATIONS > The Saberlyte2 delivers a powerhouse of performance in a minimal 1" housing for uniform distribution in narrow angle applications and small spaces. Accent, backlight and controlled narrow beam. Interior/Exterior. Wet location.

LED > VIVIO™ LED Photon Series offers the latest in advanced LED technology. Kelvin temperatures range from 2700°K to 5000°K. Choose:
AscendLED™ 90+ CRI. 4.4W or 6.5W/FT
Circadian-Safe™ patented Violet chip emission to achieve the highest CRI available. 4.4W or 6.5W/FT
RGBWW (5-in-1 Red-Green-Blue-Double White) provides two additional white LEDs, one warm and one cool, achieving a wider color spectrum. 8.5W/FT.
 Ascenti's **Circadian-Safe™ Tunable White** option allows precise color temperature control in an effort to safely maintain our natural circadian rhythm. 6.5W/FT.
 Custom lumen packages available.

LUMEN PACKAGES > Lumens vary based on wattage and CCT choices. Custom available.
 Single row choices are as follows:
 2.0 Watts/LF ("A" or "CS" single CCT, or Tunable).
 4.4 Watts/LF ("A" or "CS" single CCT, or Tunable).
 6.5 Watts/LF ("A" single CCT or Tunable).
 8.5 Watts/LF (RGBWW only).

CONSTRUCTION > Extruded aluminum housing (high grade, low copper, 6063 T5), machine milled aluminum endcaps and escutcheon plates. All electrical components are installed, wired and 100% tested prior to shipping.

MOUNTING > Choose adjustable L-Bracket, yoke (to standard 4" round J-Box) or edge mount (clip-on with set screw) condition. Luminaire may be through-wired for continuous rows.

FINISH > For white, black or other colors: 5-stage pre-treatment process with a polymer primer sealer, oven baked and top-coated with thermoset super TGIC polyester powdercoat finish. Finish is rated to meet the AAMA 605.2 performance specification which includes passing a 3000hr salt spray test for corrosion resistance.

DRIVERS > Drivers shall be remote and require engineering consultation to ensure proper loading. Maximum luminaire distance from driver is approximately 35 FT.

RATED > UL. CSA. IP 65. Wet location.

WARRANTY > 3 years.



Type: Qty: Project:

SAB2-	SABERLYTE 2
Length (Nominal, final length subject to mounting method.)	
2	2ft
3	3ft
4	4ft
6	6ft
8	8ft
C _____	Custom precise individual lengths. Enter in inches up to 96". Example C22.375"
R _____	Precise Rows over 96" . Enter entire length required in feet and inches. Example: R14'3.5". (Supplied in sections.)
Diffuser	
A	Acrylic (standard)
B	Borosilicate Glass (consult factory)
Color Temperature	
27A	2700°K AscendLED™
30A	3000°K AscendLED™
40A	4000°K AscendLED™
50A	5000°K AscendLED™
27CS	2700°K Circadian-Safe™
30CS	3000°K Circadian-Safe™
40CS	4000°K Circadian-Safe™
AMB	Amber LED
RWW	RGBWW (5-in-1 Red-Green-Blue-Warm White-Cool White)
TW	Tunable White Standard (27K- 50K)
TCS	Tunable White Circadian-Safe™ (18CS-30CS)
LTM	5-Channel Tunable Array 1650-8000K Bluetooth Enabled
CK	Custom Kelvin (contact factory)
Output	
2.0W	2.0 Watts/LF (Amber, "A" or "CS" single CCT, or Tunable)
4.4W	4.4 Watts/LF ("A" or "CS" single CCT, or Tunable)
6.5W	6.5 Watts/LF ("A" single CCT or Tunable)
8.5W	8.5 Watts/LF (RGBWW only)
Distribution	
5	5° x 120° beam
60	60° x 120° beam
Controls	
N	Non-Dimmable
O10	0-10V Dimmable Driver (120v-277v)
ELV	ELV Triac Dimmable Driver (120v-277v)
DMX	DMX Control (consult factory)
DAL	Dali Dimming
LUT	Lutron Ecosmart Dimming (consult factory)
Mounting	
LM	"L" Bracket
YM	Yoke
EM	Edge Mount (for glass, acrylic, etc.)
CM	Custom Mount (consult factory)
Housing Color	
AL	Natural Aluminum
WH	White
BK	Black
CC	Custom RAL color (consult factory)
Shield Options	
N	None
HS	Half Shield (2" extension)
FS	Full Shield (2" extension)
Shield Color	
N	None
SAL	Natural Aluminum
SBK	Black
SWH	White
SCC	Custom RAL color (consult factory)