



APPLICATIONS > The MILAD™ illuminated round mirror provides an inset, forward-facing, circular illuminated frame with integrated opal diffuser. Numerous upgrades allow for personalized and convenient customization including sensor options, USB ports, bluetooth speakers, power outlet or TV display. Optional fog-resistant, heated pad dissipates moisture, maintaining a clear image. Ideal for high-end residential, hospitality, retail, restaurant and entertainment venues.

UPGRADES >

- *Bluetooth Speaker*
- *Power Outlet*
- *USB Port*
- *Inset Makeup Magnifier*
- *Digital Time Display*
- *Heated Anti-Fog*
- *Integrated LCD TV Panel* with built-in waterproof speakers and 16:9 HD 10.4" screen

SENSOR OPTIONS > Proximity sensor activates illumination with the swipe of a hand. Sensor range: 12". Touch sensor or rocker switch also available.

LED > VIVIO™ LED Photon Series offers the latest in advanced LED technology.

Kelvin temperatures range from 2700°K to 5000°K. Choose:
 Standard 90+ CRI LEDs. *Approx. 8W/FT. 24D = 50W | 28D = 60W | 32D = 70W | 36D = 75W*
 AscendLED™ 90+ CRI, lower wattage. *4.4W or 6.5W/FT.*

Circadian-Safe™ patented Violet chip emission to achieve the highest CRI available. *4.4W/FT.*
 RGBWW (5-in-1 Red-Green-Blue-Double White) provides *two* additional white LEDs, one warm and one cool, achieving a wider color spectrum. *8.5W/FT.*

Ascenti's Circadian-Safe™ Tunable White option allows precise color temperature control in an effort to safely maintain our natural circadian rhythm. *4.4W or 6.5W/FT.*
 Custom lumen packages available.

CONSTRUCTION > Ultra-thin, silver-backed mirror, corrosion-resistant. Diamond screen protection provides wear- and scratch-resistance. Light aluminum alloy back box. 1.57" thickness (40mm). Low voltage, cool running DC power supply. 120V-277V AC 50/60Hz. All electrical components are installed, wired and 100% tested prior to shipping.

MOUNTING > Direct wall mount. Easy install. Maintenance-free.

RATED > UL. CSA. IP44.

WARRANTY > 3 years.

Type: Qty: Project:

MIL- MILAD™ Circular Illuminated Mirror

Size (nominal) Don't see your size? Just ask!

- 24D 24" Diameter (nominal)
- 28D 28" Diameter (nominal)
- 32D 32" Diameter (nominal)
- 36D 36" Diameter (nominal)
- C__ Custom (enter diameter)

Color Temperature

- 27K 2700°K Standard
- 30K 3000°K Standard
- 40K 4000°K Standard
- 50K 5000°K Standard
- 27A 2700°K AscendLED™
- 30A 3000°K AscendLED™
- 40A 4000°K AscendLED™
- 50A 5000°K AscendLED™
- 27CS 2700°K Circadian-Safe™
- 30CS 3000°K Circadian-Safe™
- 35CS 3500°K Circadian-Safe™
- RWW RGBWW (5-in-1 Red-Green-Blue-Warm White-Cool White)
- TW Tunable White Standard (27K- 50K)
- TCS Tunable White Circadian-Safe™ (18CS-30CS)
- CK Custom Kelvin or Tunable (consult factory)

Output

- 8W 8 Watts/LF (Applicable to *Standard* LED CCTs)
- 4.4W 4.4 Watts/LF (Applicable to "A" or "CS" single CCT, or Tunable)
- 6.5W 6.5 Watts/LF ("A" single CCT or Tunable)
- 8.5W 8.5 Watts/LF (RGBWW only)
- C__ Custom wattage (consult factory)

Control

- N Non-Dimmable
- O10 0-10V Dimmable Driver (120V-277V)
- ELV ELV TRIAC Dimmable Driver (120V-277V)
- DAL Dali Dimming
- DMX DMX Control (consult factory)

Switch Selection

- PS Proximity Sensor
- TS Touch Sensor
- RS Rocker Switch
- CS Custom Switch/Sensor (consult factory)

Upgrades - add to part# with + sign (TD+US +__)

- N None
- HA Heated Anti-Fog
- TD Time Display
- BS Bluetooth Speaker
- US USB Port
- PO Power Outlet
- TV Integrated TV Screen (consult factory)

