



**AILERON >** Winged Feature Sconce

**LED >** VIVIO™ LED Photon Series. Choose standard Blue emission LEDs or our patented Circadian-Safe™ Violet chip emission to achieve the highest CRI available on the market. Our RGBWW (5-in-1 Red-Green-Blue-Double White) provides *two* additional white LEDs, one warm and one cool, achieving the ultimate in color rendering customization in a single source. Ascenti's Circadian-Safe™ Tunable White option allows precise color temperature control in an effort to safely maintain our natural circadian rhythm.

**LUMEN PACKAGES >** Watts and lumens will vary depending on LED choice for the vertical linear portion as well as both accents, up/down. Please provide specification details, as well as dimming and control specifications, so we may present a custom design solution that meets your project needs.

**CONSTRUCTION >** Unique, 2-piece, wing-shaped sconce featuring luminous acrylic or cast glass wing diffuser and concave aluminum accent piece with machined aluminum endcaps. Wall wash accent LEDs in the top and bottom portion of the fixture distribute an approximate 25 degree beam, both up and down. Specify custom beam angle. 5FT, 6FT or other custom length. Integral driver. All electrical components are installed, wired and 100% tested prior to shipping.

**MOUNTING >** Wall mount.

**RATED >** UL. ETL. CSA. Damp/Wet Location.

**WARRANTY >** 3 years.



Type: Qty: Project:

<b>ALN</b>	<b>AILERON - CUSTOM WING SCONCE</b>	
	<b>Dimensions</b> (Contact Factory)	
5	5FT	Nominal length
6	6FT	Nominal length
C_____		Custom Size
	<b>Diffuser</b>	
AC	Acrylic	
GL	Cast Glass	
	<b>Linear CCT - Color Temperature</b>	
27A	2700°K	AscendLED™
30A	3000°K	AscendLED™
35A	3500°K	AscendLED™
40A	4000°K	AscendLED™
50A	5000°K	AscendLED™
27CS	2700°K	Circadian-Safe™
30CS	3000°K	Circadian-Safe™
35CS	3500°K	Circadian-Safe™
40CS	4000°K	Circadian-Safe™
RWW	RGBWW	(5-in-1 Red-Green-Blue-Warm White-Cool White)
TCS	Tunable White	Circadian-Safe™ (18CS-30CS)
CK	Custom Kelvin or Tunable	(consult factory)
	<b>Linear Output</b> (per foot)	
4.4W	4.4 Watts/LF	("A" or "CS" single CCT, or Tunable)
6.5W	6.5 Watts/LF	("A" single CCT or Tunable)
8.5W	8.5 Watts/LF	(RGBWW only)
C_____	Custom wattage	(consult factory)
	<b>Dual Accents Up/Down - CCT - Color Temperature</b>	
27A	2700°K	AscendLED™
30A	3000°K	AscendLED™
35A	3500°K	AscendLED™
40A	4000°K	AscendLED™
50A	5000°K	AscendLED™
27CS	2700°K	Circadian-Safe™
30CS	3000°K	Circadian-Safe™
35CS	3500°K	Circadian-Safe™
40CS	4000°K	Circadian-Safe™
RWW	RGBWW	(5-in-1 Red-Green-Blue-Warm White-Cool White)
	<b>Dual Accents Up/Down - Output</b> (Single/Each)	
___W	Custom Watts	(please specify per light)
	<b>Dual Accents Up/Down - Distribution</b>	
25D	25 Degree	Beam Angle
C___	Custom	Beam Angle
	<b>Voltage</b>	
U	120V - 277V	
	<b>Control</b>	
N	Non-Dimmable	
010	0-10V	Dimmable Driver (120v-277v)
ELV	ELV	Triac Dimmable Driver (120v-277v)
DMX	DMX	Control (consult factory)
DAL	Dali	Dimming
LUT	Lutron	Ecosmart Dimming (consult factory)
	<b>Finish</b>	
AL	Natural	Aluminum
CC	Custom	RAL color (consult factory)