








Low Profile



Adjustable



Spring Clips



Dimensions

cut-out

Type: Qty: Project:

**ROG-** ROGUE Downlight Series

**2R** ROGUE 2" Round

2R 2" Round Flanged

**Color Temperature**

27K 2700°K  
30K 3000°K  
40K 4000°K  
50K 5000°K  
CK Custom Kelvin

**Output**

3W 3 watts / 250 lumens

**Distribution**

SP Spot

**Control**

N Non-Dimming (1 driver ea, Constant Current)  
010 0-10V Dimmable (1 driver ea, Constant Current)  
ELV ELV Triac Dimmable (1 driver ea, Constant Current)  
DAL Dali Dimming (consult factory)  
RMCV Remote Constant Voltage Daisy-Chained  
(Produced for daisy-chaining, requires separate remote driver purchase, contact factory)

**Mounting**

SC Spring Clip  
CM Custom Mount (consult factory)

**Trim Finish**

WH White trim  
BK Black trim  
AL Natural Aluminum trim  
CC Custom RAL color (consult factory)

**APPLICATIONS >** The ROGUE DOWNLIGHT...a paradigm shift on the concept of the perfect downlight. Elegance and precision unite in this minimal 2" low-profile housing designed for accent, task or wallwash applications. Adjustable lamp for specific aiming capability.

**LED >** VIVIO™ LED Photon Series offers the latest LED technology in Kelvin temperatures ranging from 2700K to 5000K at > 90CRI.


**LUMEN PACKAGES >** Medium spot distribution with 24° beam angle. 3W. ~250 lumens. 120V. Custom lumen packages available.

**CONSTRUCTION >** Low-profile aluminum housing with adjustable lamp positioning. Spring clips for simple installation. LED is mounted to die-cast/extruded aluminum heat sink for active heat dissipation. All electrical components are installed, wired and 100% tested prior to shipping.

**FINISH >** Die-cast aluminum, white or black trim. Alternate colors are available. Consult factory.

**RATED >** Indoor Dry/Damp Location.

**WARRANTY >** 5 years.



24° spot

