



APPLICATIONS > The BAKU™ illuminated mirror provides an inset, forward-facing illuminated frame with integrated opal diffuser. Numerous upgrades allow for personalized and convenient customization including sensor options, USB ports, bluetooth speakers, power outlet or TV display. Optional fog-resistant, heated pad dissipates moisture, maintaining a clear image. Ideal for high-end residential, hospitality, retail, restaurant and entertainment venues.

UPGRADES >

- *Bluetooth Speaker*
- *Power Outlet*
- *USB Port*
- *Inset Makeup Magnifier*
- *Digital Time Display*
- *Heated Anti-Fog*
- *Integrated LCD TV Panel* with built-in waterproof speakers and 16:9 HD 10.4" screen

SENSOR OPTIONS > Proximity sensor activates illumination with the swipe of a hand. Sensor range: 12". Touch sensor or rocker switch also available.

LED > VIVIO™ LED Photon Series offers the latest in advanced LED technology.

Kelvin temperatures range from 2700°K to 5000°K. Choose:

Standard 90+ CRI LEDs. 8W/FT, approx. 230 lumens/FT.

AscendLED™ 90+ CRI, lower wattage. 4.4W or 6.5W/FT.

Circadian-Safe™ patented Violet chip emission to achieve the highest CRI available. 4.4W/FT.

RGBWW (5-in-1 Red-Green-Blue-Double White) provides two additional white LEDs, one warm and one cool, achieving a wider color spectrum. 8.5W/FT.

Ascenti's **Circadian-Safe™ Tunable White** option allows precise color temperature control in an effort to safely maintain our natural circadian rhythm. 4.4W or 6.5W/FT. Custom lumen packages available.

CONSTRUCTION > Ultra-thin, silver-backed mirror, corrosion-resistant. Diamond screen protection provides wear- and scratch-resistance. Light aluminum alloy edged frame and back box. 1.57" thickness (40mm). Low voltage, cool running DC power supply. 120V-277V AC 50/60Hz. All electrical components are installed, wired and 100% tested prior to shipping.

MOUNTING > Direct wall mount. Easy install. Maintenance-free.

RATED > UL. CSA. IP44.

WARRANTY > 3 years.

Type: Qty: Project:

BAK-	BAKU™ Illuminated Mirror	
	Size (nominal) Don't see your size? Just ask!	
3036	30"W x 36"H	
3642	36"W x 42"H	
4248	42"W x 48"H	
4848	48"W x 48"H	
6048	60"W x 48"H	
C__	Custom (enter width up to 80" x height up to 48")	
	Color Temperature	
27K	2700°K Standard	
30K	3000°K Standard	
40K	4000°K Standard	
50K	5000°K Standard	
27A	2700°K AscendLED™	
30A	3000°K AscendLED™	
40A	4000°K AscendLED™	
50A	5000°K AscendLED™	
27CS	2700°K Circadian-Safe™	
30CS	3000°K Circadian-Safe™	
35CS	3500°K Circadian-Safe™	
RWW	RGBWW (5-in-1 Red-Green-Blue-Warm White-Cool White)	
TW	Tunable White Standard (27K- 50K)	
TCS	Tunable White Circadian-Safe™ (18CS-30CS)	
CK	Custom Kelvin or Tunable (consult factory)	

	Output	
8W	8 Watts/LF (Applicable to <i>Standard</i> LED CCTs)	
4.4W	4.4 Watts/LF (Applicable to "A" or "CS" single CCT, or Tunable)	
6.5W	6.5 Watts/LF ("A" single CCT or Tunable)	
8.5W	8.5 Watts/LF (RGBWW only)	
C__	Custom wattage (consult factory)	

	Control	
N	Non-Dimmable	
010	0-10V Dimmable Driver (120V-277V)	
ELV	ELV TRIAC Dimmable Driver (120V-277V)	
DAL	Dali Dimming	
DMX	DMX Control (consult factory)	

	Frame Edging Color	
AL	Natural Aluminum	
WH	White	
CC	Custom RAL color (consult factory)	

	Switch Selection	
PS	Proximity Sensor	
TS	Touch Sensor	
RS	Rocker Switch	
CS	Custom Switch/Sensor (consult factory)	

	Upgrades - add to part# with + sign (TD+US +__)	
N	None	
HA	Heated Anti-Fog	
TD	Time Display	
BS	Bluetooth Speaker	
US	USB Port	
PO	Power Outlet	
M5	Inset Magnification Disc 5x	
M7	Inset Magnification Disc 7x	
TV	Integrated TV Screen (consult factory)	

