



8 mounting points required  
with 2 power drops

**APPLICATIONS >** Hospitality, Corporate Offices, Hospitals, Residential, Retail, Atrium, Restaurant and Entertainment Venues.

**LED >** Choose standard Blue emission LEDs or our patented Circadian-Safe™ Violet chip emission to achieve the highest CRI available.

CCT: 4000K

CRI: 95+

**OUTPUT >** 6.5 watts/ft. 244watts total.

**CONSTRUCTION >** 12ft diameter. Extruded aluminum housing (high grade, low copper, 6063 T5). Frosted acrylic diffuser. All electrical components are installed, wired and 100% tested prior to shipping.

**POWER >** Driver: (2) remote 24vdc drivers. Hanging points: 8. Power Drops: 2 (opposite sides of the circle). One thicker, single point power drop is optional.

**RATED >** UL. CSA. Damp Location.

**WARRANTY >** 3 years.

Type: Qty: Project:

**CQL-** CIRQL Custom Round Pendant

**Size** Nominal dimensions

12R 12ft diameter

**Diffuser**

WH Opal Acrylic  
C Custom Diffuser

**Color Temperature**

40K 4000°K Standard  
40CS 4000°K Circadian-Safe™

**Output**

6.5 6.5 watts per foot

**Voltage**

1 120V  
2 277V  
U 120V - 277V

**Dimming**

010 0-10V Dimmable Driver (120v-277v)  
ELV ELV Triac Dimmable Driver (120v-277v)  
DMX DMX Control (consult factory)  
DAL Dali Dimming  
LUT Lutron Ecosmart Dimming (consult factory)

**Mounting**

CS Cable Suspension (8pt stainless steel, 4' adjustable)

**Housing Color**

WH White  
BK Black  
SV Silver  
DBZ Dark Bronze  
CC Custom RAL color (consult factory)