



LED Spot: 1"  
White Square Trim: 5.4"  
Cut-out dimensions: 5.59"  
Outer Trimless Mesh: 9.25"



ROUND SQUARE

**SPECIFICATION >** Mastering minimalism for discreet applications. With a luminous area of less than 1", the REYK mini-downlight offers high performance and energy efficiency in an ingeniously tiny package. For flood accent, task or wallwash applications at a 60° beam angle. The REYK's innovative and minimally intrusive design of a mere 1-1/8" height allows for a simple installation solution in a wide range of applications.

**LED >** VIVIO™ LED Photon Series offers numerous choices in the latest LED technology. Choose standard emission LEDs for 80+ CRI or AscendLED™ for 90+CRI.

**LUMEN PACKAGES >** 16W/1400lumens per 1" fixture. 60° flood distribution. Up to 5 units may be connected in parallel.

**CONSTRUCTION >** Choose a Square or Round 1" mini-module. Visible white trim piece is 5.4" square with a trimless mesh flange at 9.25" square (for seamless drywall applications). Cut-out dimensions are 5.59" or 142mm square. Fixture is designed using lightweight, aluminum components. LED is mounted to a unique die-cast heat sink for double-sided heat dissipation. IP67 wterproof connector. Spring systems for ease of installation and COB replacement. Long service life, 100,000hrs. All electrical components are installed, wired and 100% tested prior to shipping.

**MOUNTING >** Recessed drywall application.

**FINISH >** 5-stage pre-treatment process with a polymer primer sealer, oven baked and top-coated with thermoset super TGIC polyester powdercoat finish.

**RATED >** UL. CSA. Dry/damp Location. Non-IC.

**WARRANTY >** 3 years.

Type:	Qty:	Project:
<b>RYK-</b>	<b>Reyk 1" Mini-Spotlight Series</b>	
	<b>1" Round or Square Option</b>	
	1R	Single Round
	1S	Single Square
	<b>Flange Type</b>	
	L	Trimless white flange
	<b>Color Temperature</b>	
	30K	3000°K Standard (80+ CRI)
	40K	4000°K Standard (80+ CRI)
	50K	5000°K Standard (80+ CRI)
	30A	3000°K AscendLED™ (90+ CRI)
	40A	4000°K AscendLED™ (90+ CRI)
	50A	5000°K AscendLED™ (90+ CRI)
	CK	Custom Kelvin
	<b>Output</b>	
	16W	16W / 1400 lumens
	<b>Distribution</b>	
	FL	Flood
	<b>Voltage</b>	
	U	120V-277V
	<b>Control</b>	
	N	Non-dimmable
	010	0-10V Dimmable

