








Low Profile



Adjustable



Spring Clips



Dimensions

APPLICATIONS > The ROGUE DOWNLIGHT...a paradigm shift on the concept of the perfect downlight. Elegance and precision unite in this minimal 3.5" low-profile housing designed for accent, task or wallwash applications. Adjustable lamp for specific aiming capability.

LED > VIVIO™ LED Photon Series offers numerous choices in the latest LED technology. Kelvin temperatures range from 2700K to 5000K at > 90CRI.

LUMEN PACKAGES > Medium spot distribution with 24° beam angle. 9W. ~650 lumens. 120V. Custom lumen packages available.

CONSTRUCTION > Low-profile aluminum housing with adjustable lamp positioning. Spring clips for simple installation. LED is mounted to die-cast/extruded aluminum heat sink for active heat dissipation. All electrical components are installed, wired and 100% tested prior to shipping.

FINISH > Die-cast aluminum. Alternate colors are available. Consult factory.

RATED > Indoor Dry/Damp Location.

WARRANTY > 5 years.

Type: Qty: Project:

ROG- ROGUE Downlight Series

35R ROGUE 3.5" Round

35R 3.5" Round Flanged

Color Temperature

27K 2700°K
 30K 3000°K
 40K 4000°K
 50K 5000°K
 CK Custom Kelvin

Output

9W 9 watts / 650 lumens

Distribution

SP Spot

Control


N Non-Dimming (1 driver ea, Constant Current)
 O10 0-10V Dimmable (1 driver ea, Constant Current)
 ELV ELV Triac Dimmable (1 driver ea, Constant Current)
 DAL Dali Dimming (consult factory)
 RMCV Remote Constant Voltage Daisy-Chained
 (Produced for daisy-chaining, requires separate remote driver purchase, contact factory)

Mounting

SC Spring Clip
 CM Custom Mount (consult factory)

Trim Finish

WH White trim
 BK Black trim
 AL Natural Aluminum trim
 CC Custom RAL color (consult factory)



24° spot

