



APPLICATIONS > The CYBERSCONCE 9" wall sconce offers futuristic, geometric styling in a tough-as-nails package, made to withstand the elements. CYBERSCONCE is designed for direct illumination and at a mere 2-3/4" deep, this fixture is also ADA compliant. Versatile as an interior/ exterior luminaire, CYBERSCONCE may brighten up a drab exterior garage or pathway wall, invoke drama on an interior hallway or stairwell, or even highlight hidden architectural details.

Ideal for numerous contemporary applications: Hospitality, Corporate Offices, Hospitals, High-End Residential, Retail, Atrium, Restaurant and Entertainment Venues.

LED > 1" Spot. 3W Cree XPE LED, 80+ CRI, 90 lumens, PMMA diffuser, IP67. DC12V-24V.
Beam angles: 15°, 25°, 38°, 45°, 60°
CCTs: 2700K, 3000K, 4000K, 6000K, RGB.
Contact factory for LED customization.

CONSTRUCTION > Heavy gauge aluminum housing and mounting plate. Fixture wired with UL listed electrical components for standard Class II low voltage equipment. LED light engine is a self-enclosed assembly with lens, easily replaceable by removing the shroud. All electrical components are installed, wired and 100% tested prior to shipping.

MOUNTING > Standard surface/wall mount to J-Box. Custom mounting available. Contact factory with unique project specifications.

FINISH > Satin black, silver or custom RAL color. 5-stage pre-treatment process with a polymer primer sealer, oven baked and top-coated with thermoset super TGIC polyester powdercoat finish.

DRIVERS > NON-Dimmable 12W IP67, Constant Voltage, 24Vdc, 0.50A.

RATED > UL/ETL Listed Components. Suitable for Dry/Damp location. Specify Wet location in Options.

WARRANTY > 3 years.

Type: Qty: Project:

CYB- CYBERSCONCE WALL SCONCE

Size (Nominal)

9 9"H x 4.5"W x 2.75"D Nominal

Color Temperature

27K 2700°K
30K 3000°K
40K 4000°K
60K 6000°K
RGB RGB

Distribution

15 15° beam angle
25 25° beam angle
38 38° beam angle
45 45° beam angle
60 60° beam angle

Output

3W 3W

Controls

N Non-dimming

Mounting

STD Standard wall mount to J-Box
CM Custom Mounting (contact factory)

Finish

SL Silver
BK Satin Black
CC Custom RAL color (consult factory)

Options

EXT Exterior Wet Location

