



APPLICATIONS > The RAINDROP Mini-Pendant provides 360° diffuse illumination for a variety of indoor applications as a single use accent or multi-pendant chandelier. Or have ASCENTI design a fully customized array as in this 125-piece cascade of raindrops, flowing down the entry stairway and accenting the front glass façade. ASCENTI completed the project with a custom 18ft long canopy and 125 individual cable lengths. The sky is the limit with this versatile WORLD of ONE customizable luminaire.

The RAINDROP's unobtrusive 1.32" high fixture cap tops a solid, softly frosted acrylic rod, fully illuminating the diffuser from the top to the bottom of its 12.32" form. Minimal, sophisticated styling for any application: Hospitality, Corporate Offices, High-End Residential, Retail, Atrium, Restaurant and Entertainment Venues.

LED > VIVIO™ LED Photon Series offers numerous choices in the latest LED technology. Single Kelvin temperatures range from 2700K to 5000K at 6W. Our COB RGBWW (5-in-1 Red-Green-Blue-Double White) provides two additional white LEDs, one warm white and one cool white, achieving a wider color spectrum. 2W, 90+ CRI, Range: 6500K to 2700K, 24V.

CONSTRUCTION > RAINDROP Mini-Pendant is constructed of high-grade, low-copper aluminum top cap and canopy connector. 1.5" diameter frosted acrylic rod. All electrical components are installed, wired and 100% tested prior to shipping.

MOUNTING > Cable Suspension [CS] utilizes black powercord, cut to length. Standard cable length 4'-0". For longer lengths consult factory. Custom 6-wire cord for RGBWW. The 0.45" Dia. x 0.75"H ceiling connector installs into a standard single canopy. Custom array canopies are designed per project parameters. Custom catenary system is designed per project parameters. ASCENTI to provide complete Shop Drawings with dimensioned layout and pendant placement diagram.

FINISH > Black anodized finish.

DRIVERS > Drivers provided are remote, Class II type. Quantity varies as per array, cord length and wattage. Fixture to be wired with UL listed electrical components for standard Class II low voltage equipment.

RATED > UL rated components suitable for Dry/Damp location. Specify wet location.

WARRANTY > 3 years.

Type: Qty: Project:

RD1.5	RAIN DROP 1.5" diameter
	Single Fixture or Array Quantity with custom canopy
----	Single Fixture Only (skip, no entry)
AR _____	Custom Array. Enter quantity.
	Diffuser
FA	Frosted Acrylic Solid Rod
	Color Temperature
27K	2700°K
30K	3000°K
40K	4000°K
50K	5000°K
RGBWW	Red/Green/Blue/27K/65K
	LED Output
2W	2 Watts/per pendant (RGBWW only)
6W	6 Watts/per pendant (single color)
	Control
N	Non-Dimmable
ELV	ELV Triac Dimmable Driver (120v-277v)
DMX	DMX (required for RGBWW)
	Mounting
CS4	Cable Suspension (standard 4ft lengths)
CS _____	Custom cable lengths (contact factory for array)
CAT	Custom Catenary System (contact factory)
	Finish
BA	Black Anodized Aluminum
CC	Custom finish (contact factory)
	Options
EXT	Exterior/Wet location

