



SPECIFICATION > The SALK 2' x 2' LED panel's unique design incorporates a high-transmittance LGP (light guide plate) and diffusion plate. Deploying the newest LGP technology, this lens structure provides optimal distribution uniformity, thus producing a soft and comfortable, yet effectively bright light across the entire panel.

LED > VIVIO™ LED Photon Series offers numerous choices in the latest LED technology. Choose standard emission SMD2835 LEDs at 80CRI or AscendLED™ to achieve 90+CRI.

LUMEN PACKAGES >

Standard = 40 Watts, approx 3400 Lumens
AscendLED™ = 42 Watts, approx 3600 Lumens

MOUNTING > Lay-in a standard suspended ceiling in place of a 2ft x 2ft ceiling tile, suspend via 4 aircraft cables or surface mount to wall or hard ceiling.
Dimensions: 23.465" x 23.465" x .386" high (596mm x 596mm x 9.8mm)

CONSTRUCTION > Ultra-thin, ultra-lightweight, aluminum-framed design. All electrical components are installed, wired and 100% tested prior to shipping.

RATED > UL. ETL. CSA. Indoor Dry/Damp Location.

WARRANTY > 3 years.

Type: Qty: Project:

SLK	SALK LED TRIMMED PANEL	
	Dimensions (Contact Factory)	
22	2ft x 2ft nominal	
	Diffuser	
WH	Opal White Acrylic Diffuser	
	Color Temperature	
30K	3000°K Standard (80+ CRI)	
35K	3500°K Standard (80+ CRI)	
40K	4000°K Standard (80+ CRI)	
30A	3000°K AscendLED™ (90+ CRI)	
35A	3500°K AscendLED™ (90+ CRI)	
40A	4000°K AscendLED™ (90+ CRI)	
CK	Cusom Kelvin (contact factory)	
	Output	
40W	40W / approx 3400 lumens - choose Standard CCT above	
42W	42W / approx 3600 lumens - choose AscendLED™ CCT above	
	Voltage	
U	120V - 277V	
	Control	
N	Non-Dimmable	
010	0-10V Dimmable Driver (120v-277v)	
ELV	ELV Triac Dimmable Driver (120v-277v)	
DMX	DMX Control (consult factory)	
DAL	Dali Dimming	
LUT	Lutron Ecosmart Dimming (consult factory)	
	Finish	
AL	Natural Aluminum (standard)	
CC__	Custom RAL color (consult factory)	
	Mounting	
TB	Standard T-Bar (lay-in, no mounting devices)	
CS	Cable suspension (4)	
BR	Surface mount bracket	

