



**APPLICATIONS >** The OPUS™ illuminated mirror provides an inset, forward-facing illuminated oval with integrated opal diffuser. Numerous upgrades allow for personalized and convenient customization including sensor options, USB ports, bluetooth speakers, power outlet or TV display. Optional fog-resistant, heated pad dissipates moisture, maintaining a clear image. Ideal for high-end residential, hospitality, retail, restaurant and entertainment venues.

**UPGRADES >**

- Bluetooth Speaker
- Inset Makeup Magnifier
- Integrated LCD TV Panel with built-in waterproof speakers and 16:9 HD 10.4" screen
- Power Outlet
- Digital Time Display
- USB Port
- Heated Anti-Fog

**SENSOR OPTIONS >** Proximity sensor activates illumination with the swipe of a hand. Sensor range: 12". Touch sensor or rocker switch also available.

**LED >** VIVIO™ LED Photon Series offers the latest in advanced LED technology. Kelvin temperatures range from 2700°K to 5000°K. Choose:  
**Standard** 90+ CRI LEDs. Approx. 8W/FT. Size 2432 = 45W  
**AscendLED™** 90+ CRI, lower wattage. 4.4W or 6.5W/FT.  
**Circadian-Safe™** patented Violet chip emission to achieve the highest CRI available. 4.4W/FT.  
**RGBWW** (5-in-1 Red-Green-Blue-Double White) provides two additional white LEDs, one warm and one cool, achieving a wider color spectrum. 8.5W/FT.  
 Ascenti's **Circadian-Safe™ Tunable White** option allows precise color temperature control in an effort to safely maintain our natural circadian rhythm. 4.4W or 6.5W/FT.  
 Custom lumen packages available.

**CONSTRUCTION >** Ultra-thin, silver-backed mirror, corrosion-resistant. Diamond screen protection provides wear- and scratch-resistance. Light aluminum alloy back box. 1.57" thickness (40mm). Low voltage, cool running DC power supply. 120V-277V AC 50/60Hz. All electrical components are installed, wired and 100% tested prior to shipping.

**MOUNTING >** Direct wall mount. Easy install. Maintenance-free.

**RATED >** UL. CSA. IP44.

**WARRANTY >** 3 years.

Type: Qty: Project:

<b>OPS-</b>	<b>OPUS™ Illuminated Mirror</b>	
	<b>Size (nominal)</b> Don't see your size? Just ask!	
2432	24"W x 32"H (nominal)	
C__	Custom (enter width x length)	
	<b>Color Temperature</b>	
27K	2700°K Standard	
30K	3000°K Standard	
40K	4000°K Standard	
50K	5000°K Standard	
27A	2700°K AscendLED™	
30A	3000°K AscendLED™	
40A	4000°K AscendLED™	
50A	5000°K AscendLED™	
27CS	2700°K Circadian-Safe™	
30CS	3000°K Circadian-Safe™	
35CS	3500°K Circadian-Safe™	
RWW	RGBWW (5-in-1 Red-Green-Blue-Warm White-Cool White)	
TW	Tunable White Standard (27K-50K)	
TCS	Tunable White Circadian-Safe™ (18CS-30CS)	
CK	Custom Kelvin or Tunable (consult factory)	
	<b>Output</b>	
8W	8 Watts/LF (Applicable to Standard LED CCTs)	
4.4W	4.4 Watts/LF (Applicable to "A" or "CS" single CCT, or Tunable)	
6.5W	6.5 Watts/LF ("A" single CCT or Tunable)	
8.5W	8.5 Watts/LF (RGBWW only)	
C__	Custom wattage (consult factory)	
	<b>Control</b>	
N	Non-Dimmable	
O10	0-10V Dimmable Driver (120V-277V)	
ELV	ELV TRIAC Dimmable Driver (120V-277V)	
DAL	Dali Dimming	
DMX	DMX Control (consult factory))	
	<b>Switch Selection</b>	
PS	Proximity Sensor	
TS	Touch Sensor	
RS	Rocker Switch	
CS	Custom Switch/Sensor (consult factory)	
	<b>Upgrades - add to part# with + sign (TD+US +__)</b>	
N	None	
HA	Heated Anti-Fog	
TD	Time Display	
BS	Bluetooth Speaker	
US	USB Port	
PO	Power Outlet	
M5	Inset Magnification Disc 5x	
M7	Inset Magnification Disc 7x	
TV	Integrated TV Screen (consult factory)	

