## ΛSСЕΝΤΙ

## ROGUE 3 DOWNLIGHTS

			DOWNLIGHT
	Type:	Qty:	Project:
	ROG-	ROGUE Do	wnlight Series
	3R	ROGUE 3"	Round
		3R	3" Round Flanged
		Color Temp	perature
		27K	2700°К
		30K	3000°K
		40K 50K	4000°K 5000°K
		CK	Custom Kelvin
		Output	
		6W	6 watts / 450 lumens
		Distributio	n
		SP	Spot
		Control	
		N 010	Non-Dimming (1 driver ea, Constant Current) 0-10V Dimmable (1 driver ea, Constant Current)
		ELV	ELV Triac Dimmable (1 driver ea, Constant Current)
		DAL	Dali Dimming (consult factory)
		RMCV	Remote Constant Voltage Daisy-Chained (Produced for daisy-chaining, requires separate remote driver purchase, contact factory)
		Mounting	
Low Profile Adjustable Spring Clips		SC	Spring Clip
Dimensions		CM	Custom Mount (consult factory)
2.7"		WH	White trim
		BK	Black trim
		AL	Natural Aluminum trim
····· 2.8″ ···		CC	Custom RAL color (consult factory)
cut-out			
<b>APPLICATIONS &gt;</b> The ROGUE DOWNLIGHTa paradigm shift on the concept of the perfect			
downlight. Elegance and precision unite in this minimal 3" low-profile housing designed for			
accent, task or wallwash applications. Adjustable lamp for specific aiming capability.			
LED > VIVIO™ LED Photon Series offers numerous choices in the latest LED technology. Kelvin			
temperatures range from 2700K to 5000K at > 90CRI.			
LUMEN PACKAGES > Medium spot distribution with 24° beam angle. 6W. ~450 lumens. 120V.			
Custom lumen packages available.			1252
<b>CONSTRUCTION &gt;</b> Low-profile aluminum housing with adjustable lamp positioning. Spring clips			
for simple installation. LED is mounted to die-cast/extruded aluminum heat sink for active heat			
dissipation. All electrical components are installed, wired and 100% tested prior to shipping.		$\square$	
<b>FINISH &gt;</b> Die-cast aluminum white or black. Alternate colors are available. Consult factory.			
RATED > Indoor Dry/Damp Location.			
WARRANTY > 5 years.			
		$\langle \rangle$	XXIIIXXX
		X	
			24° spot
			Mod.May.15.20

**ASCENTI**LIGHTING.COM

