



**APPLICATIONS >** At a mere 1.25" square, the SlimJim exterior bollard offers a sleek, unobtrusive and modern accent landscaping profile. Ideal for pathway, area accents and mounting between or adjacent to exterior stair rails, fence posts, trees or walls. Adjustable LED head rotates vertically 118.5° for precise aiming (28.5° up and 90° down). Heavy-duty ground spike included.

**LED >** 25-degree narrow spot distribution. 3W Cree XPE LED, 80+ CRI, 90 lumens, PMMA diffuser, IP67. DC12V-24V input voltage.  
CCT: 2700K, 3000K, 4000K or 5000K.

**CONSTRUCTION >** Post is constructed of heavy-wall 6061-T6 aluminum alloy and fixture head is of machined aluminum. Fixture wired with UL listed electrical components for standard Class II low voltage equipment. LED light engine is a self-enclosed assembly with lens, easily replaceable by accessing the face-plate. Wiring for each fixture will include a 36" pigtail to make connection to site wiring, provided by others. Contractor shall provide waterproof connections (waterproof wire nuts are acceptable) and push excess wire and connectors back up into the bollard pole. Base of bollard shall be open and fixture placed over cabling entry as required for a clean installation. All electrical components are installed, wired and 100% tested prior to shipment.

Heavy-duty, 3" wide PVC ground mount stake, included. Both brass insert options provide corrosion-resistant and wear-resistant threads. Choose 10" for most applications; choose 13" to achieve superior anchoring capability *in sandy soil only* (too deep for use with hard soils).

**FINISH >** Black anodized is standard. Contact factory for other color or finish type.

**RATED >** UL/ETL Listed Components. Suitable for Wet Location.

**WARRANTY >** 3 years.

Type: Qty: Project:

**SLIMJIM- SLIMJIM**

**Post**

22 22" height OA  
30 30" height OA  
C-XX" Custom height, specify inches

**Color Temperature**

27K 2700°K 95CRI  
30K 3000°K 95CRI  
40K 4000°K 95CRI  
50K 5000°K 95CRI

**Output**

3 12vac/dc 3 watt CREE LED  
C\_\_\_ Custom wattage, consult factory

**Distribution**

25 25-degree narrow spot beam angle  
C\_\_\_ Client to specify, consult factory

**Control**

N Non-Dimmable

**Finish**

BK Anodized Black  
CC Custom Color (indicate RAL color)

**Mount**

GM10 Ground Mount Stake, 10", PVC  
GM10B Ground Mount Stake, 10", PVC + brass insert  
GM13B Ground Mount Stake, 13", PVC + brass insert

**Order Separately:**

Exterior Power Supply Box

Enter qty required: PSB004-\_\_\_FT Exterior wet enclosure, customized for your application. Includes low-voltage driver + lead. Indicate lead length required in feet: \_\_\_\_\_



Mod.Apr.1.2022