



**APPLICATIONS >** The EK110 delivers a powerhouse of performance in a minimal housing, less than an inch wide. It's shallow 7/16" depth provides a wide, uniform 110° distribution. Ideal for small space applications: accent, backlight and wide beam for cove and perimeter illumination.

**LED >** VIVIO™ LED Photon Series offers numerous choices in the latest LED technology. Choose standard BLU™ emission LEDs or our patented Circadian-Safe™ Violet chip emission to achieve the highest CRI available, always 95+.

**LUMEN PACKAGES >**  
 600 lumens/LF and 6.2 watts/LF  
 800 lumens/LF and 8.2 watts/LF  
 1000 lumens/LF and 11.5 watts/LF  
 Custom lumen packages available.

**CONSTRUCTION >** Extruded aluminum housing (high grade, low copper, 6063 T5). All electrical components are installed, wired and 100% tested prior to shipping.

**MOUNTING >** Choose Standard Surface Mount or Adjustable U-Bracket which allows 106° fixture rotation for precise aiming. Adds an additional 1-3/16" height. Luminaire may be through-wired for continuous rows.

**FINISH >** Anodized aluminum or white powdercoat finish.

**DRIVERS >** Drivers shall be remote and require engineering consultation to ensure proper loading.

**RATED >** UL. CSA. Indoor Dry/Damp Location.

**WARRANTY >** 3 years.

Type: Qty: Project:

<b>EK11-</b>	<b>EK 110</b>
<b>Length (Nominal)</b>	
24	24"
36	36"
48	48"
C__	Custom (enter length)
<b>Diffuser</b>	
W	Opal Acrylic
CL	Clear Acrylic
<b>Color Temperature</b>	
30K	3000°K Standard
30CS	3000°K Circadian-Safe™
40K	4000°K Standard
40CS	4000°K Circadian-Safe™
<b>Output</b>	
600L	600 lumens/LF 6.2 watts/LF
800L	800 lumens/LF 8.2 watts/LF
1000L	1000 lumens/LF 11.5 watts/LF
CL__	Custom lumen package
<b>Distribution</b>	
110D	110° beam
<b>Voltage</b>	
1	120V
2	277V
U	120V - 277V
<b>Mounting</b>	
SM	Surface Mount
UM	"U" Bracket (adjustable to 106° angles)
CM	Custom Mount (consult factory)
<b>Housing Color</b>	
AL	Natural Aluminum
WH	White
CC	Custom RAL color (consult factory)

